

# EL-AVIOR MTW TRACK

## PRODUCT DESCRIPTION


|                                      |                                                                                                                                           |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>MOUNTING</b>                      | Suspended or ceiling surfaced lighting track system (suitable for GLOBAL Trac)                                                            |
| <b>LIGHT SOURCE</b>                  | LED                                                                                                                                       |
| <b>OPTICAL SYSTEM</b>                | Facet reflector (FRE)                                                                                                                     |
| <b>LIGHT DISTRIBUTION</b>            | Direct                                                                                                                                    |
| <b>WIRING</b>                        | Electronic control gear                                                                                                                   |
| <b>MATERIALS</b>                     | Housing: die cast aluminium + sheet steel<br>Reflector: facet anodized aluminium                                                          |
| <b>SURFACE FINISH</b>                | Housing: black (RAL 9005)<br>Other colours on request                                                                                     |
| <b>ACCESSORIES</b>                   | Various types of connections and suspension equipment (GLOBAL Trac)<br>On request:<br>Various coloured filters<br>Exchangeable reflectors |
| <b>SERVICE LIFETIME</b>              | 50,000 hours / L70                                                                                                                        |
| <b>AMBIENT OPERATING TEMPERATURE</b> | Up to +35 °C                                                                                                                              |

## FEATURES

- Manually controlled Tunable White (push button control)
- Two operating variants: Discreet mode (steps 2750 K / 3000 K / 3500 K / 4000 K / 4500 K / 5000 K / 5500 K / 6000 K) or Smooth mode (2700 K - 5700 K)

## AREAS OF APPLICATION

Boutiques, galleries, museums, receptions, shops, showrooms



## MAIN IMAGE



## PRODUCT DETAILS



## STANDARD



## LIST OF PRODUCTS

| TYPE + OPTICAL SYSTEM  | NO. LIGHT SOURCES X POWER | LIGHT SOURCE / LED MODULE | CONTROL GEAR |
|------------------------|---------------------------|---------------------------|--------------|
| EL-AVIOR MTW TRACK 40° | 1x31W                     | LED 1600-1850lm/927-957   | LED DRIVER   |
| EL-AVIOR MTW TRACK 60° | 1x31W                     | LED 1600-1850lm/927-957   | LED DRIVER   |
| EL-AVIOR MTW TRACK 24° | 1x31W                     | LED 1600-1850lm/927-957   | LED DRIVER   |

